

Package: edgebundle (via r-universe)

August 26, 2024

Title Algorithms for Bundling Edges in Networks and Visualizing Flow and Metro Maps

Version 0.4.2

Description Implements several algorithms for bundling edges in networks and flow and metro map layouts. This includes force directed edge bundling <[doi:10.1111/j.1467-8659.2009.01450.x](https://doi.org/10.1111/j.1467-8659.2009.01450.x)>, a flow algorithm based on Steiner trees<[doi:10.1080/15230406.2018.1437359](https://doi.org/10.1080/15230406.2018.1437359)> and a multicriteria optimization method for metro map layouts <[doi:10.1109/TVCG.2010.24](https://doi.org/10.1109/TVCG.2010.24)>.

URL <https://github.com/schochastics/edgebundle>,
<https://schochastics.github.io/edgebundle/>

BugReports <https://github.com/schochastics/edgebundle/issues>

License MIT + file LICENSE

Suggests testthat (>= 2.0.0), network, tidygraph

Config/testthat/edition 2

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

LinkingTo Rcpp

Imports Rcpp, igraph, reticulate, interp

Depends R (>= 3.5)

Repository <https://schochastics.r-universe.dev>

RemoteUrl <https://github.com/schochastics/edgebundle>

RemoteRef HEAD

RemoteSha c339f1e392d51b036a6b24eff300caf1ea6f894

Contents

cali2010	2
convert_edges	3
edge_bundle_force	3
edge_bundle_hammer	5
edge_bundle_path	6
edge_bundle_stub	7
install_bundle_py	9
metro_berlin	9
metro_multicriteria	10
tnss_dummies	11
tnss_smooth	12
tnss_tree	13
us_flights	14
us_migration	15
Index	16

cali2010

Migration from California in 2010

Description

A dataset containing the number of people who migrated from California to other US states

Usage

cali2010

Format

igraph object

Source

<https://www.census.gov/data/tables/time-series/demo/geographic-mobility/state-to-state-migration.html>

convert_edges	<i>Convert edges</i>
---------------	----------------------

Description

converts edges of an igraph/network/tidygraph object into format useable for edge bundling

Usage

```
convert_edges(object, coords)

## Default S3 method:
convert_edges(object, coords)

## S3 method for class 'igraph'
convert_edges(object, coords)

## S3 method for class 'network'
convert_edges(object, coords)

## S3 method for class 'tbl_graph'
convert_edges(object, coords)
```

Arguments

object	graph object
coords	coordinates of vertices

Value

data frame of edges with coordinates

Author(s)

David Schoch

edge_bundle_force	<i>force directed edge bundling</i>
-------------------	-------------------------------------

Description

Implements the classic edge bundling by Holten.

Usage

```
edge_bundle_force(  
  object,  
  xy,  
  K = 1,  
  C = 6,  
  P = 1,  
  S = 0.04,  
  P_rate = 2,  
  I = 50,  
  I_rate = 2/3,  
  compatibility_threshold = 0.6,  
  eps = 1e-08  
)
```

Arguments

object	a graph object (igraph/network/tbl_graph)
xy	coordinates of vertices
K	spring constant
C	number of iteration cycles
P	number of initial edge divisions
S	initial step size
P_rate	rate of edge divisions
I	number of initial iterations
I_rate	rate of iteration decrease per cycle
compatibility_threshold	threshold for when edges are considered compatible
eps	accuracy

Details

This is a re-implementation of <https://github.com/upphiminn/d3.ForceBundle>. Force directed edge bundling is slow ($O(E^2)$).

see [online](#) for plotting tips

Value

data.frame containing the bundled edges

Author(s)

David Schoch

References

Holtén, Danny, and Jarke J. Van Wijk. "Force-Directed Edge Bundling for Graph Visualization." *Computer Graphics Forum* (Blackwell Publishing Ltd) 28, no. 3 (2009): 983-990.

See Also

[edge_bundle_hammer](#), [edge_bundle_stub](#), [edge_bundle_path](#)

Examples

```
library(igraph)
g <- graph_from_edgelist(
  matrix(c(
    1, 12, 2, 11, 3, 10,
    4, 9, 5, 8, 6, 7
  ), ncol = 2, byrow = TRUE), FALSE
)
xy <- cbind(c(rep(0, 6), rep(1, 6)), c(1:6, 1:6))
edge_bundle_force(g, xy)
```

edge_bundle_hammer *hammer edge bundling*

Description

Implements the hammer edge bundling by Ian Calvert.

Usage

```
edge_bundle_hammer(object, xy, bw = 0.05, decay = 0.7)
```

Arguments

object	a graph object (igraph/network/tbl_graph)
xy	coordinates of vertices
bw	bandwidth parameter
decay	decay parameter

Details

This function only wraps existing python code from the datashader library. Original code can be found at <https://gitlab.com/ianjcalvert/edgehammer>. Datashader is a huge library with a lot of dependencies, so think twice if you want to install it just for edge bundling. Check https://datashader.org/user_guide/Networks.h for help concerning parameters bw and decay. To install all dependencies, use [install_bundle_py](#).

see [online](#) for plotting tips

Value

data.frame containing the bundled edges

Author(s)

David Schoch

See Also

[edge_bundle_force](#), [edge_bundle_stub](#), [edge_bundle_path](#)

edge_bundle_path *Edge-Path Bundling*

Description

Implements edge-path bundling.

Usage

```
edge_bundle_path(  
  g,  
  xy,  
  max_distortion = 2,  
  weight_fac = 2,  
  segments = 20,  
  bundle_strength = 1,  
  mode = "out"  
)
```

Arguments

g	an igraph object
xy	coordinates of vertices
max_distortion	maximum distortion
weight_fac	edge weight factor
segments	number of subdivisions of edges
bundle_strength	bundle strength factor
mode	the parameter fo shortest_paths

Details

This is a re-implementation of <https://github.com/mwallinger-tu/edge-path-bundling>
see [online](#) for plotting tips

Value

data.frame containing the bundled edges

Author(s)

David Schoch

References

Wallinger, M., Archambault, D., Auber, D., Nollenburg, M., & Peltonen, J. (2021). Edge-Path Bundling: A Less Ambiguous Edge Bundling Approach. IEEE Transactions on Visualization and Computer Graphics.

See Also

[edge_bundle_hammer](#), [edge_bundle_stub](#), [edge_bundle_force](#)

Examples

```
library(igraph)
g <- graph_from_edgelist(matrix(c(
  1, 2, 1, 6,
  1, 4, 2, 3, 3, 4, 4, 5, 5, 6
), ncol = 2, byrow = TRUE), FALSE)
xy <- cbind(c(0, 10, 25, 40, 50, 50), c(0, 15, 25, 15, 0, -10))
edge_bundle_path(g, xy)
```

edge_bundle_stub	<i>stub edge bundling</i>
------------------	---------------------------

Description

Implements the stub edge bundling by Nocaj and Brandes

Usage

```
edge_bundle_stub(
  object,
  xy,
  alpha = 11,
  beta = 75,
  gamma = 40,
  t = 0.5,
  tshift = 0.5
)
```

Arguments

object	a graph object (igraph/tbl_graph). Does not support network objects
xy	coordinates of vertices
alpha	maximal angle (in degree) between consecutive edges in a bundle
beta	angle (in degree) at which to connect two stubs
gamma	maximal overall angle (in degree) of an edge bundle
t	numeric between 0 and 1. control point location
tshift	numeric between 0 and 1. The closer to one, the longer the bigger bundle

Details

see [online](#) for plotting tips

Value

data.frame containing the bundled edges

Author(s)

David Schoch

References

Nocaj, Arlind, and Ulrik Brandes. "Stub bundling and confluent spirals for geographic networks." International Symposium on Graph Drawing. Springer, Cham, 2013.

See Also

[edge_bundle_hammer](#), [edge_bundle_force](#), [edge_bundle_path](#)

Examples

```
library(igraph)
g <- graph.star(10, "undirected")

xy <- matrix(c(
  0, 0,
  cos(90 * pi / 180), sin(90 * pi / 180),
  cos(80 * pi / 180), sin(80 * pi / 180),
  cos(70 * pi / 180), sin(70 * pi / 180),
  cos(330 * pi / 180), sin(330 * pi / 180),
  cos(320 * pi / 180), sin(320 * pi / 180),
  cos(310 * pi / 180), sin(310 * pi / 180),
  cos(210 * pi / 180), sin(210 * pi / 180),
  cos(200 * pi / 180), sin(200 * pi / 180),
  cos(190 * pi / 180), sin(190 * pi / 180)
), ncol = 2, byrow = TRUE)

edge_bundle_stub(g, xy)
# use ggforce::geom_bezier for plotting
```

install_bundle_py *install python dependencies for hammer bundling*

Description

install datashader and scikit-image

Usage

```
install_bundle_py(method = "auto", conda = "auto")
```

Arguments

method	Installation method (by default, "auto" automatically finds a method that will work in the local environment, but note that the "virtualenv" method is not available on Windows)
conda	Path to conda executable (or "auto" to find conda using the PATH and other conventional install locations)

metro_berlin *Subway network of Berlin*

Description

A dataset containing the subway network of Berlin

Usage

```
metro_berlin
```

Format

igraph object

References

Kujala, Rainer, et al. "A collection of public transport network data sets for 25 cities." Scientific data 5 (2018): 180089.

metro_multicriteria *Metro Map Layout*

Description

Metro map layout based on multicriteria optimization

Usage

```
metro_multicriteria(object, xy, l = 2, gr = 0.0025, w = rep(1, 5), bsize = 5)
```

Arguments

object	original graph
xy	initial layout of the original graph
l	desired multiple of grid point spacing. ($l \cdot gr$ determines desired edge length)
gr	grid spacing. ($l \cdot gr$ determines desired edge length)
w	weight vector for criteria (see details)
bsize	number of grid points a station can move away from its original position

Details

The function optimizes the following five criteria using a hill climbing algorithm:

- *Angular Resolution Criterion*: The angles of incident edges at each station should be maximized, because if there is only a small angle between any two adjacent edges, then it can become difficult to distinguish between them
- *Edge Length Criterion*: The edge lengths across the whole map should be approximately equal to ensure regular spacing between stations. It is based on the preferred multiple, l , of the grid spacing, g . The purpose of the criterion is to penalize edges that are longer than or shorter than lg .
- *Balanced Edge Length Criterion*: The length of edges incident to a particular station should be similar
- *Line Straightness Criterion*: (not yet implemented) Edges that form part of a line should, where possible, be co-linear either side of each station that the line passes through
- *Octilinearity Criterion*: Each edge should be drawn horizontally, vertically, or diagonally at 45 degree, so we penalize edges that are not at a desired angle see [online](#) for more plotting tips

Value

new coordinates for stations

Author(s)

David Schoch

References

Stott, Jonathan, et al. "Automatic metro map layout using multicriteria optimization." IEEE Transactions on Visualization and Computer Graphics 17.1 (2010): 101-114.

Examples

```
# the algorithm has problems with parallel edges
library(igraph)
g <- simplify(metro_berlin)
xy <- cbind(V(g)$lon, V(g)$lat) * 100

# the algorithm is not very stable. try playing with the parameters
xy_new <- metro_multicriteria(g, xy, l = 2, gr = 0.5, w = c(100, 100, 1, 1, 100), bsize = 35)
```

 tnss_dummies

Sample points for triangulated networks

Description

uses various sampling strategies to create dummy nodes for the [tnss_tree](#)

Usage

```
tnss_dummies(
  xy,
  root,
  circ = TRUE,
  line = TRUE,
  diag = TRUE,
  grid = FALSE,
  rand = FALSE,
  ncirc = 9,
  rcirc = 2,
  nline = 10,
  ndiag = 50,
  ngrid = 50,
  nrand = 50
)
```

Arguments

xy	coordinates of "real" nodes
root	root node id
circ	logical. create circular dummy nodes around leafs.
line	logical. create dummy nodes on a straight line between root and leafs.
diag	logical. create dummy nodes diagonally through space.

grid	logical. create dummy nodes on a grid.
rand	logical. create random dummy nodes.
ncirc	numeric. number of circular dummy nodes per leaf.
rcirc	numeric. radius of circles around leaf nodes.
nline	numeric. number of straight line nodes per leaf.
ndiag	numeric. number of dummy nodes on diagonals.
ngrid	numeric. number of dummy nodes per dim on grid.
nrand	numeric. number of random nodes to create.

Value

coordinates of dummy nodes

Author(s)

David Schoch

Examples

```
# dummy nodes for tree rooted in California
xy <- cbind(state.center$x, state.center$y)
xy_dummy <- tnss_dummies(xy, 4)
```

 tnss_smooth

Smooth a Steiner tree

Description

Converts the Steiner tree to smooth paths

Usage

```
tnss_smooth(g, bw = 3, n = 10)
```

Arguments

g	Steiner tree computed with tnss_tree
bw	bandwidth of Gaussian Kernel
n	number of extra nodes to include per edge

Details

see see [online](#) for tips on plotting the result

Value

data.frame containing the smoothed paths

Author(s)

David Schoch

Examples

```
xy <- cbind(state.center$x, state.center$y)[!state.name %in% c("Alaska", "Hawaii"), ]
xy_dummy <- tnss_dummies(xy, root = 4)
gtree <- tnss_tree(cali2010, xy, xy_dummy, root = 4, gamma = 0.9)
tree_smooth <- tnss_smooth(gtree, bw = 10, n = 10)
```

tnss_tree

*Create Steiner tree from real and dummy points***Description**

creates an approximated Steiner tree for a flow map visualization

Usage

```
tnss_tree(
  g,
  xy,
  xydummy,
  root,
  gamma = 0.9,
  epsilon = 0.3,
  elen = Inf,
  order = "random"
)
```

Arguments

<code>g</code>	original flow network (must be a one-to-many flow network, i.e star graph). Must have a weight attribute indicating the flow
<code>xy</code>	coordinates of "real" nodes
<code>xydummy</code>	coordinates of "dummy" nodes
<code>root</code>	root node id of the flow
<code>gamma</code>	edge length decay parameter
<code>epsilon</code>	percentage of points kept on a line after straightening with Visvalingam Algorithm
<code>elen</code>	maximal length of edges in triangulation
<code>order</code>	in which order shortest paths are calculated ("random", "weight", "near", "far")

DetailsUse [tnss_smooth](#) to smooth the edges of the tree

Value

approximated Steiner tree from dummy and real nodes as igraph object

Author(s)

David Schoch

References

Sun, Shipeng. "An automated spatial flow layout algorithm using triangulation, approximate Steiner tree, and path smoothing." AutoCarto, 2016.

Examples

```
xy <- cbind(state.center$x, state.center$y)[!state.name %in% c("Alaska", "Hawaii"), ]
xy_dummy <- tnss_dummies(xy, root = 4)
gtree <- tnss_tree(cali2010, xy, xy_dummy, root = 4, gamma = 0.9)
```

us_flights

Flights within the US

Description

A dataset containing flights between US airports as igraph object

Usage

```
us_flights
```

Format

igraph object

Source

<https://gist.githubusercontent.com/mbostock/7608400/raw>

us_migration

Migration within the US 2010-2019

Description

A dataset containing the number of people migrating between US states from 2010-2019

Usage

us_migration

Format

data.frame

Source

<https://www.census.gov/data/tables/time-series/demo/geographic-mobility/state-to-state-migration.html>

Index

* datasets

cali2010, 2

metro_berlin, 9

us_flights, 14

us_migration, 15

cali2010, 2

convert_edges, 3

edge_bundle_force, 3, 6–8

edge_bundle_hammer, 5, 5, 7, 8

edge_bundle_path, 5, 6, 6, 8

edge_bundle_stub, 5–7, 7

install_bundle_py, 5, 9

metro_berlin, 9

metro_multicriteria, 10

tnss_dummies, 11

tnss_smooth, 12, 13

tnss_tree, 11, 12, 13

us_flights, 14

us_migration, 15