

Package: oaqc (via r-universe)

November 3, 2024

Title Computation of the Orbit-Aware Quad Census

Version 2.0.0

Maintainer David Schoch <david@schochastics.net>

Description Implements the efficient algorithm by Ortmann and Brandes (2017) <doi:10.1007/s41109-017-0027-2> to compute the orbit-aware frequency distribution of induced and non-induced quads, i.e. subgraphs of size four. Given an edge matrix, data frame, or a graph object (e.g., 'igraph'), the orbit-aware counts are computed respective each of the edges and nodes.

URL <https://github.com/schochastics/oaqc>

BugReports <https://github.com/schochastics/oaqc/issues>

Depends R (>= 3.4)

Suggests igraph, knitr, rmarkdown, testthat (>= 3.0.0)

License GPL (>= 3)

Encoding UTF-8

LazyData true

NeedsCompilation yes

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.2

VignetteBuilder knitr

Config/testthat/edition 3

Repository <https://schochastics.r-universe.dev>

RemoteUrl <https://github.com/schochastics/oaqc>

RemoteRef HEAD

RemoteSha ef0117d7a7b5e2632c3a122fde859e3645b49ddb

Contents

annotate_result	2
as.edge_list	2
oaqc	3

Index**4**

annotate_result	<i>Annotates the igraph object with orbit labels.</i>
-----------------	---

Description

Annotates the igraph object with orbit labels.

Usage

```
annotate_result(graph, orbits, non_ind_freq)
```

Arguments

graph	Unmodified input graph.
orbits	List with n_orbits, e_orbits matrices.
non_ind_freq	A flag indicating whether non-induced frequencies have to be written or not.

Value

orbits if the input is not an igraph, the annotated igraph instead.

as.edge_list	<i>Coerce graph input.</i>
--------------	----------------------------

Description

Coerce graph input.

Usage

```
as.edge_list(graph)
```

Arguments

graph	A matrix, data.frame or graph object.
-------	---------------------------------------

Value

Edge list matrix.

`oaqc`*Orbit-aware Quad Census computation*

Description

Implements the efficient algorithm by Ortmann and Brandes (2017) [doi:10.1007/s4110901700272](https://doi.org/10.1007/s4110901700272) to compute the orbit-aware frequency distribution of induced and non-induced quads, i.e. subgraphs of size four. Given an edge matrix, data frame, or a graph object (e.g., 'igraph'), the orbit-aware counts are computed respective each of the edges and nodes.

Usage

```
oaqc(graph, non_ind_freq = F, file = "")
```

Arguments

<code>graph</code>	A matrix, data.frame or graph object.
<code>non_ind_freq</code>	A flag indicating whether non-induced frequencies have to be returned or not.
<code>file</code>	Name (and location) of the file to be written.

Value

orbit-aware quad census on a node and edge level. Consult `vignette('oaqc')` to see the correspondence between orbit and quad.

Author(s)

Maintainer: David Schoch <david@schochastics.net> ([ORCID](#))

Authors:

- Mark Ortmann
- Felix Schoenenberger

Examples

```
k4 <- data.frame(
  source = c(0, 0, 0, 1, 1, 2),
  target = c(1, 2, 3, 2, 3, 3)
)

k4orbits <- oaqc(k4, non_ind_freq = TRUE)
print(k4orbits)
```

Index

`annotate_result`, [2](#)

`as.edge_list`, [2](#)

`oaqc`, [3](#)

`oaqc-package (oaqc)`, [3](#)